



THIS FORM IS TO BE COMPLETED ONLY BY AN AUTHORIZED NASA TECH CENTER OR AUTHORIZED NASA TECH

VEHICLE EXTERIOR / ELECTRICAL

- Electrical cutoff switch function
- Rear Tow Hook/Bar or Chassis Access
- Rain light functions
- Gel/non-spillable battery
- No bent suspension
- PFM front a-arms pinned

ENGINE COMPARTMENT

- Clean
- Coolant overflow
- Oil overflow
- No antifreeze in cooling system
- No fluid leaks
- Battery secured / bracket welds
- Battery positive terminal covered
- Starter positive terminal covered
- Cutoff switch terminals covered
- No loose wires
- Condition of hoses
- Brake fluid level/condition
- Engine mounts
- Fuel hoses braided
- Gear oil not leaking significantly

ROLL HOOP

- Chassis number plate or stamp
- Main hoop welds
- inspect welds
- General condition
- HD-Padding on contact areas (FM)
- Broomstick test - open cars
(Helmet must clear)

DRIVER COMPARTMENT

- Ballast mounted securely to chassis
- Camera and Radio secure
- Head rest padding (FM only)
- Head can't hit MSD (FM only)

DRIVER SEAT

- General condition of foam and covering
- Clearanced for HANS

BRAKES

- Brake fluid level/condition
- Pedal pressure
- Lines (condition)

HARNESSES

- SFI 16.1 or 16.5 manufacture date less than two years old **OR** FIA expiration date on belts
- Mounting points
- Submarine belt mounting
- Condition of webbing
- Harnesses threaded three times

FIRE SYSTEM

- Control securely mounted & not pinned
- 5 lb minimum, full
- AFFF/Halon 1301/1211
- Nozzles in driver compartment
- Nozzles in engine bay
- Securely mounted
- Service date and gauge filling

FUEL TANK / CELL

- Cell manufacture date _____
- Cell inspection date _____
- One way vent installed
- General condition
- Filler cap secure
- Cell FIA FT-3 with expiration proof (receipt, photo, or certificate accepted as proof)

DRIVER GEAR AND EQUIPMENT

- Suit rated SFI 3.2/A1, FIA 8856-2000, FIA 8856-1986, or FIA NORME 1986/1986
- Helmet rated SA2000, SFI 31.1A, 31.2A, 31.1/2005, FIA 8860-2004
- Face-shield condition
- Shoes rated SFI/FIA, no holes
- Gloves rated SFI/FIA, no holes
- Fire resistant underwear
- Fire resistant socks
- Fire resistant balaclava
- Head and neck restraint system rated SFI 38.1 – inspect mounts
- Arm restraint system

DRIVER EMERGENCY EXIT TIME

- Exit within 10 seconds starting in as-raced condition

GRAPHICS

- Cutoff switch sticker
- Fire bottle sticker
- Legible numbers on contrasting background
- NASA stickers (front, & both sides)
- FCC sticker on front
- Goodyear stickers on sides
- Mazda stickers on engine cover sides
- Redline Oil on sides

Season annual valid for: _____

Inspector Name

Vehicle Log Book Number

Signature or Shop Stamp:

Date: